CONSTRUCTION LEGEND	CONSTRUCTION NOTES	STANDARD PLANS	CONVENTIONAL SYMBOLS
ITEMS UNDERLINED TO BE CONSTRUCTED	CHECKED BOXES ARE FOR ITEMS APPLICABLE TO THIS PROJECT	CDDWC 2000 EDITION	EXISTING PROPOSED TOPOGRAPHY IMPROVEMENTS
1) PORTLAND CEMENT CONCRETE CURB AND GUTTER	<ul><li>1. PRIME CONTRACTOR LICENSE REQUIRED: CLASS A OR C12.</li><li>2. STANDARD PLANS REFERENCED ARE PER THE STANDARD PLANS FOR</li></ul>	SPPWC. 2009 EDITION	CURB AND GUTTER \====================================
(2) PORTLAND CEMENT CONCRETE CURB	PUBLIC WORKS CONSTRUCTION (SPPWC) UNLESS OTHERWISE NOTED.	205-2 SEWER MANHOLE ADJUSTMENT 206-2 MANHOLE RAISING RINGS	GUTTER \====\
3 ASPHALT CONCRETE CURB	3. PRIOR TO RESURFACING WITH RBAC OR ARHM, FILL ALL HOLES AND CRACKS WIDER THAN 1/4" WITH SS-1h EMULSIFIED ASPHALT AND		PAVEMENT CONCRETE
(4) PORTLAND CEMENT CONCRETE LONGITUDINAL GUTTER	SAND. PAYMENT SHALL BE CONSIDERED AS INCLUDED IN THE CONTRACT UNIT PRICE FOR RUBBERIZED ASPHALT CONCRETE OR		AC
5 PORTLAND CEMENT CONCRETE SIDEWALK, 4" THICK	ASPHALT RUBBER HOT MIX).		CURB RAMP
(6) PORTLAND CEMENT CONCRETE SIDEWALK, 6" THICK	☐ 4. PRIOR TO RESURFACING WITH AC. FILL ALL HOLES AND CRACKS WITH SS-1h EMULSIFIED ASPHALT AND SAND. PAYMENT SHALL BE		BUILDING
7) PORTLAND CEMENT CONCRETE PAVEMENT ON BASE MATERIAL	CONSIDERED AS INCLUDED IN THE CONTRACT UNIT PRICE FOR		BARRICADE ====================================
8 ASPHALT CONCRETE PAVEMENT	AC PAVEMENT.  5. REPLACE AND RELOCATE TRAFFIC SIGNAL AND STREET LIGHTING		FENCE
9 ASPHALT CONCRETE PAVEMENT ON BASE MATERIAL	PULL BOXES AFFECTED BY CURB RAMP AND SIDEWALK CONSTRUCTION.  PAYMENT WILL BE MADE AT THE CONTRACT UNIT PRICE FOR NO. 6		GUY POLE $\Phi$
10 ASPHALT CONCRETE PAVEMENT, VARIABLE THICKNESS	PULL BOX.	STATE OF CALIFORNIA. 2006 EDITION	DRIVEWAY J.M. M.
11) STABILIZATION GEOTEXTILE	☐ 6. FURNISH AND PLANT 15 GALLON TREE, PER STD PLAN 520-3 <u>CRAPE MYRTLE</u> , DOUBLE STAKING PER STD PLAN 5 <u>18-2.</u> IN TREE WELLS		FIRE HYDRANT
12 SLURRY SEAL	WITH COVERS PER <u>519-2</u> , TYPE 3, CASE 3. ☐ 7. ELEVATIONS SHOWN ARE IN FEET BASED ON OTTERBEIN.		GUARDRAIL
13 COLD MILL ASPHALT CONCRETE PAVEMENT	1995 ADJUSTMENT, NAVD 1988 DATUM.		MANHOLE ©
14) DRIVEWAY, TYPE, Y= VAR UNLESS OTHERWISE SHOWN	■ 8. ELEVATIONS SHOWN ARE IN FEET ABOVE MEAN SEA LEVEL BASED ON L.A. COUNTY BASELINE 1995 ADJUSTMENT, NGVD 1988 DATUM.		PIPE CONNECTOR PIPE
(15) ALLEY INTERSECTION (ON 6" CMB)	E.A. COUNTY DASELINE 1333 ADOUGHMENT NOVO 1300 BATOM	NON-STANDARD ABBREVIATIONS	MAIN LINE £========
(16) CROSS GUTTER (ON 6" CMB)			POLE
17 RETAINING STRUCTURE		COM COMMERCIAL RES RESIDENTIAL	PROPERTY LINE ————————————————————————————————————
18) DRAINAGE SYSTEM AS SHOWN ON SHEET INDICATED		BW BACK OF WALK	PULL BOX
(19) REINFORCED CONCRETE STAIRWAY			RAILROAD ####################################
20 CURB RAMP PER CALTRANS STD PLAN			RR XING PROTECTION ⊗
(21) CONCRETE BUS PAD			SHRUB ~~~~~~
(22) ASPHALT RUBBER HOT MIX (ARHM)			SIDEWALK  SHADED IF NOT CONTINUOUS
			SIGNAL CONTROL BOX
RUBBERIZED ASPHALT CONCRETE (RBAC), VARIABLE THICKNESS  OR ASPHALT RUBBER HOT MIX (ARHM), VARIABLE THICKNESS			SIGNAL FLASHING ©
(24) FURNISH AND PLANT TREE (PER CONSTRUCTION NOTE 6)			TRAFFIC グ LOOP
DROP CROTCH TRIM AND ROOT PRUNE TREE, FURNISH AND INSTALL ROOT CONTROL BARRIER		REFERENCES	STREET LIGHT $\diamondsuit$
26 ADJUST MANHOLE	CONSTRUCTION SYMBOLS	1) MATERIALS TEST REPORT, LAB NO. 37137,	PALM TREE
27 DOUBLE ADJUST MANHOLE	(NO) INDICATES WORK PER CONSTRUCTION LEGEND	DATED MARCH 01. 2007.	OAK TREE
28 RECONSTRUCT MANHOLE			OTHER TREE
(29) TREE WELL COVERS, TYPE 3, CASE 3	(Ltr) CURVE DATA SHOWN IN TABLE ON PLAN		VALVE 5
2	2" P4 ABOVE LINE: INDICATES THE TYPE OF STANDARD OR THICKNESS OF SURFACE MATERIAL IN		VAULT □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
31) PARKWAY DRAIN. INLET TYPE S =	INCHES; STD PLAN VARIABLES; CURB RAMP CASE, TYPE, SECTION AND DETAIL; OR TREE		CONCRETE WALL ==================================
32 RUBBERIZED EMULSION AGGREGATE SLURRY	PLANTING CASE  ()BELOW LINE: REFERENCE TO DETAIL OR THICKNESS OF BASE		STONE WALL SESSES
33 CHAIN LINK FENCE AND GATES, H= UNLESS OTHERWISE SHOWN	5" CMB BELOW LINE: REFERENCE TO DETAIL OR THICKNESS OF BASE MATERIAL IN INCHES OR TREE WELL CASE		TOP OF SLOPE
w 34) METAL BEAM GUARD RAIL	5 ABOVE LINE: $a = LENGTH$ PARALLEL TO CURB $b = LENGTH$ PERPENDICULAR TO CURB		TOE OF SLOPE
(35) TERMINAL SYSTEM END TREATMENT (TYPE AS SHOWN)	D = ELMOTH FERT ENDICOLAR TO CORD		STAND PIPE
3 TREE WELL AND COVERS, TYPE 3, CASE 3	REMOVE TREE		
80 (70) ASPHALT RUBBER AGGREGATE MEMBRANE (ARAM)	(14) arove line: $a = WIDTH OF DRIVEWAY BEHIND APRON$		AC PAVEMENT CLASS AND GRADE LEGEND
3 & 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	14) a, b above line: a = WIDTH OF DRIVEWAY BEHIND APRON b = DISTANCE BACK OF APRON		
	BELOW LINE: THICKNESS AND TYPE OF SURFACE MATERIALS BEHIND APRON		P1 C2 - PG <u>64-10</u> P3 B - PG <u>64-10</u> B - PG <u>64-10</u>
E I	בור DF LINE: STA OF THE DRIVEWAY APRON  SISTEMATION STA OF THE DRIVEWAY APRON		P2 C2 - PG 64-10 P4 D2 - PG 64-10
NO N	(19)C, L, S, R, T ABOVE LINE: STD PLAN VARIABLES		
· · · · · · · · · · · · · · · · · · ·	LEFT OF LINE: STA OF THE STAIRWAY		
	RIGHT OF LINE: STAIRWAY WIDTH AND TYPE		
S S S S S S S S S S S S S S S S S S S	∑ × ×		PH078887
A. THO	MT W MEDIAN TAPER PER STD PLAN 140-2	O PROFESSIONAL E	COUNTY OF LOS ANGELES DEPARTMENT OF PUBLIC WORKS
A DE		SUNG H. KIM	COLIMA ROAD, ET AL PHASE 2
	MF W MEDIAN FLARE PER STD PLAN 141-1	Wo. <u>C 46694</u>   Exp. <u>6-30-11</u>	NOTES AND REFERENCES
OMAS	O- RU UTILITY TO BE RELOCATED BY OTHERS	OF CALIFORNI	PROJECT ID NO. RDC0015339
A. THO		DATE MK DESCRIPTION Lylow.	a)
O 4		DATE MK DESCRIPTION  REVISIONS  PROJECT ENGINEER	
			"AS BUILT DRAWINGS"

DATE. SDATES TIME. STIMES FILE. SFILES